HEAT PRESS

SISER TS-DUE HEAT PRESS

PNEUMATIC FUNCTION, DOUBLE PLATE



Dimensions

Dimensions (closed):	94 x 78 x 72 cm (w x d x h)
Dimensions (open)	94 x 78 x 72 cm (w x d x h)
Weight	139kg

Specifications

Power	2000 watt
Voltage	220 volt 50Hz single phase
Transfer area	40 x 50 cm
Platen size	100 x 70 x 80 cm (w x d x h)
Operative area	100 x 80 cm
Basement area	60 x 70 cm
Max Temp	250°C
Contact pressure	1,2-1,5 Kg/cm^2 (2,5 – 10 bar)
Platen options	platens for caps platens 15 × 15 cm

Optional Items

- Plates for caps
- Logo platens 15x15 cm

Certified

The TS-DUE machine, as it is equipped with electrical parts operating at a voltage between 50 V and 1000 V, is subject to the Low Voltage Directive 2014/35/UE (formerly 2006/95/CE) and the Electromagnetic Compatibility Directive 2004/108/CEE.

The design and construction of the TS-DUE has been made in compliance with the essential safety requisites foreseen by Directive 2006/42/CE

| OVERVIEW |

TS DUE is an automatic heat press providing a pneumatic function and a double supporting plate, suitable for all kinds of applications on textiles (heat transfer vinyl, plastisol, sublimation).

After transferring, the machine opens automatically. Operating safety is always ensured thanks to the buttons 'Start' and 'Emergency – Stop'. Its versatility allows the operator to print on objects with a maximum thickness of 50 mm (aluminium, ceramics…)

Printing plates (15 x 15 cm or 15 x 38 cm) and cap sets are optional and available at extra cost.

It requires air compressor (NOT included) with airflow of 200 liters per minute and pressure of at least 8 bar.

| KEY FEATURES |

- Dual working stations for maximum productivity
- Automatic pneumatic operation for consistent results
- Automatic side opening heated platen
- Large 40 × 50 cm professional platen
- Digital temperature & timer controls
- Consistent pnumatic pressure
- Suitable for garments and rigid items up to 50 mm thick
- Two-hand start buttons and emergency stop for enhanced safety
- Compatible with interchangeable platens and cap accessories
- Designed for demanding commercial and industrial production environments

flamefast | EDUCATION
Engineering Equipment for Education

* Images are for reference only and may differ from the final product
** Flamefast reserves the right to change product specification without prior notice

2024_V1

Flamefast UK Ltd is accredited by:

T: 01925 281 230 • E: sales@flamefast.co.uk
W: www.flamefast.co.uk